

PRODUCT SPEC SHEET

Drive-In Racking

Highest-density LIFO system in our catalogue. Forklift drives INTO the lane. No aisles between bays. Standard in cold storage and same-SKU bulk operations.

Technical Specifications

Specification	Standard	Heavy	Max-Bay
Pallets deep	4	6	8-10
Levels high	3-5	4-6	5-7
Density vs selective	+75%	+90%	+95%
Pallet capacity	2,500 lb	2,500 lb	3,000 lb
Lane capacity	30,000 lb	45,000 lb	60,000+ lb
Post profile	3" structural	3" structural	3.5" structural
Slab spec	6" min	6", 4000 PSI	8", 4000 PSI
Lead time	2-3 weeks	3-4 weeks	5-6 weeks

Where this system wins

Cold storage / freezer. Lowers cubic footage requiring HVAC. Standard in -20°C freezer and 2°C cooler operations.

Same-SKU bulk. Each lane stores one SKU end-to-end. Common in beverage, frozen food, seasonal-bulk operations.

Slow-moving inventory. Pallets sit for weeks-to-months. LIFO ordering matters less; cube efficiency matters most.

Compliance & Lead Time

Lead time: 2-3 weeks (Standard) · 3-4 weeks (Heavy) · 5-6 weeks (Max-Bay)

Standards: CSA A344-17 aligned · ANSI MH16.1 (RMI) certified · Bill 41 documented · WSIB Insured · MLITSD-Ready inspection format

Engineering: P.Eng stamps available under separate engagement for projects requiring municipal permits or seismic-rated buildings.

Ready to install? Send your floor plan and we'll send a stamped CAD layout + itemized quote within 5 business days.

Get a Quote →
416industrial.com/get-a-quote.html
(647) 692-4416