

PRODUCT SPEC SHEET

Push-Back Racking

+90% density vs selective. 2-6 pallets deep, LIFO. Single-aisle forklift access. Best for same-SKU bulk operations and cold storage.

Technical Specifications

Specification	2-Deep	4-Deep	6-Deep
Pallets deep	2	4	6
Density vs selective	+50%	+75%	+90%
Pallet capacity	2,500 lb	2,500 lb	2,500 lb
Lane capacity	5,000 lb	10,000 lb	15,000 lb
Rail slope	3°	3.5°	4°
Frame depth	Lane + 12"	Lane + 12"	Lane + 16"
Lead time	5-7 business days	10-14 business days	3-4 weeks
Install crew size	3-4	3-4	4-5

Where this system wins

Same-SKU high volume. When you store many pallets of one SKU at a time. 4-6 pallets in the depth of one selective bay.

Cold storage. Compresses pallet positions into less square footage — major HVAC savings.

3PL fulfillment. Inventory for clients with predictable replenishment cycles. Maximizes cube without sacrificing single-aisle access.

Compliance & Lead Time

Lead time: 5-7 business days (2-deep) · 10-14 business days (4-deep) · 3-4 weeks (6-deep)

Standards: CSA A344-17 aligned · ANSI MH16.1 (RMI) certified · Bill 41 documented · WSIB Insured · MLITSD-Ready inspection format

Engineering: P.Eng stamps available under separate engagement for projects requiring municipal permits or seismic-rated buildings.

Ready to install? Send your floor plan and we'll send a stamped CAD layout + itemized quote within 5 business days.

Get a Quote →
416industrial.com/get-a-quote.html
(647) 692-4416