

PRODUCT SPEC SHEET

# Selective Pallet Racking

The most common pallet racking system in North America. 100% selectivity, every pallet position independently accessible. Field-adjustable beam levels in 2" increments. Standard 3-5 day lead times.

## Technical Specifications

Specification	Standard Duty	Heavy Duty	Structural
<b>Frame height</b>	8'-30'	8'-40'	8'-45'
<b>Post profile</b>	3" teardrop	3" teardrop	3" C-channel
<b>Post gauge</b>	14ga	13ga	11ga
<b>Beam pair capacity</b>	2,000 lb	3,800 lb	5,000+ lb
<b>Frame capacity</b>	16,000 lb	24,000 lb	40,000 lb
<b>Beam length</b>	96"/108"/120"	96"/108"/120"	96"/108"/144"
<b>Beam connector</b>	Pin + safety clip	Pin + safety clip	Bolted
<b>Finish</b>	Powder-coat	Powder-coat	Galv or powder-coat
<b>Lead time</b>	3-5 business days	5-7 business days	2-3 weeks

## Where this system wins

**Mixed-velocity SKUs.** When you need to pick any pallet at any time. 100% selectivity means every pallet directly accessible.

**High picking frequency.** E-commerce, parts distribution, food-service distribution — anywhere pick frequency > 50 pallets/day per aisle.

**Variable pallet sizes.** Beam levels field-adjustable in 2" increments. Heights reconfigured as SKU profile evolves.

## Compliance & Lead Time

**Lead time:** 3-5 business days (Standard Duty) · 5-7 business days (Heavy Duty) · 2-3 weeks (Structural)

**Standards:** CSA A344-17 aligned · ANSI MH16.1 (RMI) certified · Bill 41 documented · WSIB Insured · MLITSD-Ready inspection format

**Engineering:** P.Eng stamps available under separate engagement for projects requiring municipal permits or seismic-rated buildings.

**Ready to install?** Send your floor plan and we'll send a stamped CAD layout + itemized quote within 5 business days.

**Get a Quote** →

[416industrial.com/get-a-quote.ht](https://416industrial.com/get-a-quote.html)

[ml](https://416industrial.com/get-a-quote.html)

(647) 692-4416